

LOLLIPOP PROBE THERMOMETER



Product Description

FlashCheck Lollipop Min/Max Thermometer is an ideal waterproof tool for commercial dishwashers. Its auto-calibration and min/max features allow users to verify and quantify the final rinse temperature in commercial warewashers and dishwashers quickly.

This thermometer also measures the temperature of food that is being cooked, cooled or held, with its small-diameter probe ideal for measuring the temperature of "thin mass" food such as meat patties and chicken/fish fillets as according to FDA Food Code 4-302.12 (B). Additionally, it complies to HACCP requirements as well.

Apart from the food industry, this thermometer can also be applicable to other industries where high level of moisture is present or where minimum or maximum memory is required.

Industries Served

- Aerospace
- Electronics
- Engineering
- Food
- Healthcare
- Pharmaceutical
- Research



STREAM PEAK INTERNATIONAL PTE LTD
Tel: +65 6610 7921 | Fax: +65 6862 2520
Email: enquiry@streampeak.com.sg

Valuing Relationships, Protecting Goods
Address: 26 Tuas South Street 3, S(638026)
Website: www.streampeak.com.sg

Key Features

- NSF certified
- °F/°C selectable
- Min/Max memory stores lowest/highest readings
- Automatic calibration feature
- IP65 Waterproof housing
- Small-diameter probe ideal for measuring temperature of "thin mass" food such as meat patties and chicken/fish fillets (FDA Food Code 4-302.12 (B))
- Reduced Tip Probe



Product Specifications

Technical Specifications	
Measurement Range	-40°F to 311°F (-40°C to 155°C)
Operating Range	32°F to 122°F (0°C to 50°C)
Accuracy	±2°F (-40°F to -4°F); ±1°C (-40°C to -20°C) ±1°F (-4°F to 131°F); ±0.5°C (-20°C to 55°C) ±2°F (131°F to 311°F); ±1°C (55°C to 155°C) or ±1%, whichever is greatest
Sensor	Thermistor
Display Resolution	0.1°F /°C
Display Reading Update	1 second
Display Window Size	0.77 in W x 0.37 in H (19.5 mm W x 9.5 mm H)
Calibration	Factory calibrated to NIST traceable standards
Battery	Button Cell Alkaline
Body Casing	ABS plastic
Probe Dimensions	4.13" L x 0.14" Dia, Reduced tip 0.1" Dia (105 mm L x 3.56 mm Dia, Reduced tip 2.5 mm Dia)
Weight	1.25 oz. (35.4 gm)
Waterproof Rating	IP65
Certification	CE, RoHS, NIST traceable, manufacturers certificate of compliance available

Related Products



TRIX-8



WarmMark Duo



Hygrometer



ColdMark

